(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization International Bureau





(43) International Publication Date 29 December 2004 (29.12.2004)

PCT

(10) International Publication Number WO 2004/113771 A2

(51) International Patent Classification7:

F16J

(21) International Application Number:

PCT/US2004/019596

(22) International Filing Date: 18 June 2004 (18.06.2004)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data: 60/480,722

20 June 2003 (20.06.2003) US

- (71) Applicant (for all designated States except US): EL-LIOTT COMPANY [US/US]; 901 North Fourth Street, Jeannette, PA 15644-1473 (US).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): LI, Jiming [CN/US]; 140 Monticello Drive, Monroeville, PA 15146 (US). DE CHOUDHURY, Pranabesh [US/US]; 1354 Conway Street, Greensburg, PA 15601 (US).
- (74) Agents: BYRNE, Richard, L. et al.; Webb Ziesenheim Logsdon, Orkin & Hanson, 700 Koppers Building, 436 Seventh Avenue, Pittsburgh, PA 15219-1818 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

without international search report and to be republished upon receipt of that report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: HYBRID ABRADABLE LABYRINTH DAMPER SEAL



(57) Abstract: An apparatus for restricting axial leakage flow along a rotating shaft comprises an abradable labyrinth seal and an adjacent damper seal. Normally, the abradable labyrinth is upstream of the damper seal and there is a plurality of labyrinth and damper seal segments adjacent and interleaved along the shaft.